

Tyrone Camarero Specifications

Tyrone[®]

Camarero SA600TR-12

Key features

- Single AMD Opteron™ 6000 series (6300P ready) processors (Socket G34)16/12/8/4-Core ready support HT3.0 Link support
- AMD chipset SR5650 + SP5100
- Up to 256GB DDR3 1600MHz ECC Registered DIMM; 8x DIMM sockets
- Two Intel® 82574L controllers, Dual-Port Gigabit Ethernet
- 6x SATA2 3.0 Gbps Ports via AMD SP5100 controller, RAID 0, 1, 10
- 1 PCI-E 2.0 x8 (in x16 slot), 1 PCI-E 2.0 x8, 1 PCI-E 2.0 x4 (in x8 slot) 3 PCI
- Integrated Matrox G200 Graphics
- IPMI 2.0 with Dedicated LAN support
- 2 x 3.5" fixed drive bay
- 1 x 10cm blower
- 260W Multi-output power supply



Processor/Cache

Processor	Single AMD Opteron™ 6000 series (6300P ready) processors (Socket G34)16/12/8/4-Core ready support HT3.0 Link support
-----------	--

Chipset

Chipset	AMD chipset SR5650 + SP5100
---------	-----------------------------

System Memory

Memory Capacity	Eight DIMM sockets. Supports up to 256GB Registered ECC or 64GB Unbuffered ECC/non-ECC DDR3 600/1333/1066 SDRAM in 8 DIMMs. Quad channel memory bus
-----------------	---

Expansion Slots

PCI-Express	1 PCI-E 2.0 x8 (in x16 slot), 1 PCI-E 2.0 x8, 1 PCI-E 2.0 x4 (in x8 slot) 3 PCI
-------------	---

Integrated On-Board

SATA	AMD SP5100 (RAID 0, 1, 10)
LAN	2 RJ45 LAN ports, 1 RJ45 Dedicated LAN supports IPMI

Add-on Options

Raid Card	Optional
Optical Drive	None

Front Panel

LED Indicators	2 Network Activity LEDs, Fan Fail/System Over Heat LED, HDD activity LED, Power Status LED
Buttons	Power On/Off button System Reset button

Drive Bays

HDD Bays	2 x 3.5" fixed drive bay
----------	--------------------------

Power Supply

260W Multi-output power supply

Cooling System

1 x 10cm blower

Form Factor

Form Factor	1U Rackmount
Height	: 1.7" (43 mm),
Width	: 16.8" (426 mm),
Depth	: 14" (356 mm)

Email : info@tyronesystems.com

**For more/current product information, visit
www.tyronesystems.com**