Tyrone Camarero Specifications

Camarero SDA100C3R-28

Key features

- Dual AMD EPYC[™] 7003/7002 Series Processors Socket SP3, Up to 64 Cores
- System on Chip
- 16 DIMM slots, Supports up to 4TB Registered ECC DDR4 3200MHz SDRAM
- 3 PCI-E 4.0 x16 slots, 3 PCI-E 4.0 x8 slots, M.2 Interface: 1 PCI-E 4.0 x4, M.2 Form Factor: 2280, 22110, M.2 Key: M-key
- 10 SATA3, 2 SATADOM, 4 NVMe
- 🍨 Dual 10GBase-T LAN ports, 1 dedicated IPMI LAN Port / Dual Gigabit LAN ports,
- 1 dedicated IPMI LAN Port ASPEED AST2600 BMC graphics
- 2 USB 2.0 ports (rear), 4 USB 3.0 ports (2 rear, 2 headers)
- 8x 4-pin PWM Fans & Speed control
- 8 x 3.5"" hot-swap SAS3/SATA drive bay, 2 x 3.5"" fixed drive bay
- 3 x 80mm Hot-swap PWM Fans

| Processor/Cache | | Front Panel |
|----------------------------|---|-----------------|
| Processor | Dual AMD EPYC™ 7003/7002 Series Processors Socket SP3, Up to 64 Cores | LEDs |
| | | Buttons |
| Chipset | | Drive Bays |
| Chipset | System on Chip | HDD Bays |
| System Memor | у | Peripheral Driv |
| Memory Capacity | 16 DIMM slots, Supports up to 4TB | Power Suppl |
| Memory capacity | Registered ECC DDR4 3200MHz SDRAM | 600/800/100 |
| Expansion Slot | S | |
| PCI-Express | 3 PCI-E 4.0 x16 slots, 3 PCI-E 4.0 x8 slots, | Cooling System |
| | M.2 Interface: 1 PCI-E 4.0 x4, M.2 Form Factor: 2280, 22110, M.2 Key: M-key | 3 x 80mm H |
| | | Form Factor |
| ntegrated O | nboard | |
| SATA | 10 SATA3 (6 Gbps) ports | Form Factor |
| LAN | Dual 10GBase-T LAN ports, 1 dedicated IPMI LAN Port / Dual Gigabit LAN ports, 1 dedicated IPMI LAN Port | Dimensions: |
| Add-on Opti | ons | |
| | | E |
| Raid Card Optical Drive | Optional Optional | For more |



rone

| LEDs | 2 Network Activity LEDs, HDD activity LED, Power Status LED, Power Fail LED, System Information LED | |
|----------------------------|--|--|
| Buttons | Power On/Off button, System Reset Butto | |
| Drive Bays | | |
| HDD Bays | 8 x 3.5"" hot-swap SAS3/SATA drive bay, 2 x 3.5"" fixed drive bay | |
| Peripheral Drive | Optional 1 x slim DVD-ROM drive bay, Optional 2 x USB 2.0 ports, Optional 1 x COM port tray, Optional 2 x USB 3.0 port | |
| Power Supply | | |
| 600/800/1000 | W Redundant Power Supply | |
| Cooling Syste | m | |
| 3 x 80mm Hot | t-swap PWM Fans | |
| F F | | |
| Form Factor | | |
| Form Factor | 2U Rackmount | |
| | 2U Rackmount Height : 3.5"" (89 mm), Width : 17.2"" (437 mm) , Depth : 25.5"" (647 mm) | |
| Form Factor Dimensions: | Height : 3.5"" (89 mm), Width : 17.2"" (437 mm) , | |

www.tyronesystems.com

AMD the AMD logo inside are trademarks of Advanced Micro Devices in US and / Or other Countries

ons subject to change without notice. Picture used for representation purpose only and the actual product may differ in looks. All other brands and names are the property of their respective owners