Tyrone Camarero Specifications

Camarero: SDA200A3H-460

Key Feature

- AMD EPYC™ 9004 series Processors, Dual Socket SP5 supported, CPU TDP supports Up to 400W TDP
- Up to 6TB 3DS ECC RDIMM, DDR5-4800MHz in 24 DIMM slots
- Integrated IPMI 2.0 + KVM with dedicated LAN
- 32x SATA3 Hybrid via MCIO, 1 AIOM slot
- ASPEED AST2600 BMC graphics via I/O board
- 10 PCle 5.0 x8 MCIO connectors
- 4x USB 3.0 ports (2 rear via I/O board + 2 via header)
- 60 x 2.5""/3.5"" Top loading Bays (SAS/SATA) with 2 x 30 drive expander
- 12 x 2.5"/3.5" Rear Bays (SAS/SATA/NVMe) with direct attached backplane"
- 2000W(80 Plus Titanium Redundant PSUs)







Processor/Cache

AMD EPYC™ 9004 series Processors, Dual **Processor**

Socket SP5 supported, CPU TDP supports

Up to 400W TDP

Chipset

Chipset System On Chip

System Memory

Memory Capacity Up to 6TB 3DS ECC RDIMM, DDR5-4800MHz in 24 DIMM slots

Expansion Slot

PCI-Express 1 PCIe 5.0 x16 Right Riser Slot,

1 PCIe 5.0 x16 Left Riser Slot M.2 Interface: 2 PCle 3.0 x4

Integrated Onboard

LAN 1 Dedicated IPMI LAN port

Add-on Options

Raid Card Optional

Optical Drive

None

Drive bays

HDD Bays 60 x 2.5""/3.5"" Top loading Bays

(SAS/SATA) with 2 x 30 drive expander

backplane

12 x 2.5"/3.5" Rear Bays (SAS/SATA/NVMe) with direct

attached backplane

Power Supply

2000W(80 Plus Titanium Redundant **Power Supply**

PSUs)

Cooling System

1 AOC cooling Fan(s) (optional)

5 counter-rotation PWM 40x40x56mm Fan(s)

Form Factor

Form Factor 4U Rackmount

Dimensions

Dimensions 1046.4*446.2*175.7 (D x W x H)

1191.5*446.2*175.7 (D x W x H)

(with CMA)

Email: Info@tyronesystems.com For more/current product information, Visit www.tyronesystems.com

AMD the AMD logo inside are trademarks of Advanced Micro Devices in US and / Or other Countries
Specifications subject to change without notice. Picture used for representation purpose only and the actual product may differ in looks. All other brands and names are the property of their respective owners