Tyrone Camarero Specifications

Tyrone

Camarero-SDI100C2TP-26

Key Feature

High Performance Computing, Hyper-Converged Infrastructure, Big Data / Big Science Four hot-pluggable systems (nodes) in a 2U form factor. Each node supports the following:

- "Dual Socket P+ (LGA-4189) 3rd Generation Intel® Xeon® Scalable Processors
- . .
- Intel® C621A chipset
- "16 DIMMs, Up to 4TB 3DS ECC DDR4-3200 LRDIMM/RDIMM
- . .
- 1 PCle 4.0 x16 (LP), 1 PCle 4.0 x8 (with M.2 adapter installed for support 2 NVME up to 22x80 mm)
- Intel® X710 Dual port 10GBase-T LAN onboard
- 6x 2.5" hot-swap SATA/SAS drive bays
- 4 heavy duty 8cm PWM fans with optimal fan speed control (Per System)
- Two 2200W redundant power supplies with PMBus
- "ASPEED AST2600 BMC, 2 USB, VGA. RoT, Broadcom® 3908 SAS (12Gbps); 6 slots per node; RAID 0, 1, 5, 6, 10, 50 support





Processor/Cache

Processor

"Dual Socket P+ (LGA 4189) 3rd Gen Intel® Xeon® Scalable processors,Up to 32C/64T; Up to 48MB Cache per CPU, Supports up to 185W TDP CPUs (Air Cooled)"

System Memory

Memory Capacity Memory Capacity: 16 DIMM slots,Up to 4TB: 16x 256 GB DRAM,Memory Type: 3200/2933/2666MHz ECC DDR4 RDIMM

Chipset

Chipset

Intel® C621A chipset

Expansion Slot

PCI-Express

1 PCle 4.0 x16 (LP), 1 PCle 4.0 x8 (with M.2 adapter installed for support 2 NVME up to

22x80 mm)

Integrated Onboard:

SATA

Intel® C621A controller for 6 SATA3 (6 Gbps)

ports; RAID 0,1,5,10

Network

Connectivity: 2x 10GbE BaseT with Intel® X710-AT2"

IPMI:

Support for Intelligent Platform Management Interface v.2.0, IPMI 2.0 with virtual media over

LAN and KVM-over-LAN support

Add-on Options

Raid Card

None

Optical Drive None

Front Panel

LED

Network activity LED, Power status LED, System information(overheat /UID) LEDstatus, System information

Buttons

Power On/Off button, UID button"

Drive bays

HDD Bays

6x 2.5" hot-swap SATA/SAS drive bays

Power Supply

Power Supply

2200W Redundant, Titanium Level

Power Supply

Cooling System

Fans

"4 heavy duty 8cm PWM fans with optimal fan speed control (Per System)"

Form Factor

Form Factor

2U Rackmount

Dimensions

Dimensions

"Dimensions:Height: 3.47""

(88mm), Width: 17.25"" (438mm), Depth

: 28.75"" (730mm)"

Email: Info@tyronesystems.com
For more/current product information, Visit
www.tyronesystems.com

Intel, the Intel logo, the Intel Inside logo, Xeon, and Intel Xeon Phi are trademarks of Intel Corporation in the U.S and/Or other Countries

Specifications subject to change without notice. Picture used for representation purpose only and the actual product may differ in looks. All other brands and names are the properties of their respective owners