Tyrone Camarero Specifications

Camarero SDI10C2R-224

Key features

- 3rd Gen Intel[®] Xeon[®] Scalable processors Dual Socket LGA-4189 (Socket P+) supported, CPU TDP supports Up to 185W TDP, 2 UPI up to 11.2 GT/s
- Intel® C621A
- Up to 2TB RDIMM, DDR4-3200MHz; Up to 2TB 3DS ECC LRDIMM, DDR4-3200MHz, in 8 DIMM slots
- 4 PCI-E 4.0 x16, M.2 Interface: 2 PCI-E 4.0 x4, M.2 Form Factor: 2280/22110, 2280, M.2 Key: M-Key
- Intel® C621A controller for 12 SATA3 (6 Gbps) ports; RAID 0,1,5,10
- Dual LAN with Intel® i210 Gigabit Ethernet Controller/ Dual LAN with Intel® X550 10GBase-T Ethernet Controller
- 1 VGA port
- 24 x 2.5" hot-swap SAS/SATA drive bay, optional 2 x 2.5" hot-swap drive bay
- 3x 8cm high-performance PWM fan(s) Optional 5x 6cm 4pin high performance fan(s)
- 920W Redundant Platinum power supply





Processor/Cache

3rd Gen Intel® Xeon® Scalable processors, Processor

Dual Socket LGA-4189 (Socket P+) supported, CPU TDP supports Up to 185W TDP, 2 UPI

up to 11.2 GT/s

Chipset

Chipset Intel® C621A

System Memory

Up to 2TB RDIMM, DDR4-3200MHz; **Memory Capacity**

Up to 2TB 3DS ECC LRDIMM, DDR4-3200MHz, in 8 DIMM slots

Expansion Slots

PCI-Express 4 PCI-E 4.0 x16, M.2 Interface: 2 PCI-E 4.0 x4,

M.2 Form Factor: 2280/22110, 2280, M.2

Key: M-Key,

Integrated Onboard

SATA Intel® C621A controller for 12 SATA3 (6 Gbps)

ports; RAID 0,1,5,10

2 RJ45 Gigabit Ethernet LAN ports / optional: IAN

2 RJ45 10 Gigabit Ethernet LAN ports

Add-on Options

Raid Card Optional

Optical Drive None Front Panel

LEDs Power status LED, HDD activity LED,

> 2 Network Activity LEDs, Unit Identification (UID) LED ,Fan Fail/System Over Heat LED

Buttons Power On/Off button System Reset button

Drive Bays

24x 2.5"" hot-swap SAS/SATA drive bay, **HDD Bays**

Optional 2x 2.5"" hot-swap drive bay

Power Supply

920W Redundant Platinum power supply

Cooling System

Fans: 3x 8cm high-performance PWM fan(s), Optional 5x 6cm 4pin high performance fan(s)

Form Factor

Form Factor 2U Rackmount

Dimensions: Height-3.5" (89 mm),

> Width-17.2" (437 mm), Depth - 24.8" (630 mm)

Email: info@tyronesystems.com For more/current product information, visit www.tyronesystems.com

intel, the Intel logo, the Intel Inside logo, Xeon, and Intel Xeon Phi are trademarks of intel Corporation in the U.S and/Or other Countries