

Tyrone Camarero Specifications

Tyrone

Camarero- SDI200C3R-28

Key features

- Virtualization, Enterprise Server, Application and data serving, Compute Intensive Applications
- Dual Socket E (LGA-4677) 5th/4th Gen Intel® Xeon® Scalable processors, supports up to 350W TDP
- 16 DIMM slots, Up to 4TB DDR5-4800MHz ECC Registered RDIMM
- 2 PCIe 5.0 x8 LP slot(s), 4 PCIe 5.0 x16 LP slot(s)
- Dual ports 1G LAN/Dual ports 10G LAN
- 8 x 3.5" hot-swap SAS3/SATA drive bay
- 3 middle 8cm Fan(s)
- 600W/650W/800W/1200W Redundant Power supply



Processor/Cache

Processor Dual Socket E (LGA-4677) 5th/4th Gen Intel® Xeon® Scalable processors, supports up to 350W TDP

Chipset

Chipset Intel® C741 Chipset

System Memory

Memory Capacity Memory Capacity: 16 DIMM slots ,Up to 4TB: 16x 256 GB DRAM, Memory Type: 4800MHz ECC DDR5 RDIMM

Expansion Slots

PCI-Express 2 PCIe 5.0 x8 LP slot(s), 4 PCIe 5.0 x16 LP slot(s)

Integrated On-Board

SATA SATA3 (6Gbps)

Network Connectivity Dual ports 1G LAN/Dual ports 10G LAN

Add-on Options

Raid card Optional

Optical Drive Optional

Front Panel

LED HDD activity, Network activity, Power status, System information (overheat/UID)

Buttons Power On/Off button, System Reset button

Drive bays

Drive bays 8 x 3.5" hot-swap SAS3/SATA drive bay.

Peripheral bays 1x slim DVD drive bays (optional)

Power Supply

Power Supply 600W/650W/800W/1200W Redundant Power supply

Cooling System

Fans 3 middle 8cm Fan(s)

Form Factor

Form Factor 2U Rackmount

Dimensions

Dimensions Height - 3.5" (89mm), Width 17.2" (437mm) Depth 25.5" (647mm).

Email : Info@tyronesystems.com

For more/current product information, Visit

www.tyronesystems.com