

Tyrone Camarero Specifications

Tyrone

Camarero- SDI200C3R-48

Key Feature

Virtualization, Enterprise Server, Application and data serving, Compute Intensive Applications

- Dual socket (LGA-4677) 4th and 5th Gen Intel Xeon Scalable Processors, supports up to 300W TDP
- Intel® C741
- 16 DIMM slots, Up to 4TB DDR5-4800MHz ECC Registered RDIMM
- 4 PCIe 5.0 x16 full height slot(s), 2 PCIe 5.0 x8 full height slot(s)
- 2x 1GbE port(s) /2x 10GbE port(s)
- 8x 3.5"/2.5" hot-swap SAS/SATA bays, 2 NVMe M.2 slots
- 2 rear Fan(s), 3 middle Fan(s)
- 1200W Redundant Titanium Level power supplies
Optional : 1200W Single Power Supply.



Processor/Cache		Drive bays	
Processor	Dual socket (LGA-4677) 4th and 5th Gen Intel Xeon Scalable Processors, supports up to 300W TDP	HDD Bays	8x 3.5"/2.5" hot-swap SAS/SATA bays, 2 NVMe M.2 slots
System Memory		Peripheral Bays	2x 5.25" DVD bays (optional)
Memory Capacity	16 DIMM slots, Up to 4TB DDR5-4800MHz ECC Registered RDIMM	Power Supply	
Chipset		Power Supply	1200W Redundant Titanium Level power supplies Optional : 1200W Single Power Supply.
Chipset	Intel C741® Chipset	Cooling System	
Expansion Slot		Fans	2 rear Fan(s), 3 middle Fan(s)
PCI-Express	4 PCIe 5.0 x16 full height slot(s), 2 PCIe 5.0 x8 full height slot(s)	Form Factor	
Integrated Onboard:		Form Factor	4U Rackmount
SATA	SATA3 (6Gbps)	Dimensions	
Network Connectivity	2x 1GbE port(s) / 2x 10GbE port(s)	Dimensions	Height:17.8" (452mm), Width :7" (178mm), Depth:25.5" (647mm)
Add-on Options		Email : Info@tyronesystems.com For more/current product information, Visit www.tyronesystems.com	
Raid Card :	Optional		
Optical Drive :	Optional		