

Tyrone Camarero Specifications

Tyrone

Camarero: SDI200C3S-212H

Key Feature

2U front-loading storage server with 12 hot-swap 3.5" SAS/SATA bays (SAS hardware RAID; 6 optional NVMe) and PCIe 5.0

Enterprise Server, iSCSI SAN, HPC, Data Center, Database Processing & Storage, Corporate Database, Appliance Optimized Storage Building Blocks



- Dual Socket E (LGA-4677) 5th/4th Gen Intel® Xeon® Scalable processors
- Up to 4TB 3DS ECC RDIMM, DDR5-5600MT/s(1DPC) in 16 DIMM slots
- 2x 10 GbE onboard via Broadcom BCM57416, 1x GbE Dedicated LAN for server remote management: IPMI 2.0 / KVM over LAN / Media over LAN
- 12x 3.5"/2.5" Hot-swap SAS3/SATA3 drives, 2x Rear 2.5" SATA Slots, 2x NVMe M.2 (form factor: 2280 and 22110)
- 3x 8cm hot-swap counter-rotate redundant PWM cooling fans
- 1200W Redundant Power Supplies Titanium Level (96%)
- HW RAID support via Broadcom® 3916

Processor/Cache	Drive bays
<p>Processor Dual Socket E (LGA-4677), 5th Gen Intel® Xeon® / 4th Gen Intel® Xeon® Scalable processors</p>	<p>HDD Bays 12x 3.5"/2.5" Hot-swap SAS3/SATA3 drives, 2x Rear 2.5" SATA Slots, 2x NVMe M.2 (form factor: 2280 and 22110) front hot-swap 3.5" SAS/SATA drive bay(s), 2 rear hot-swap 2.5" SATA drive bay(s) Option A: Total 6 bay(s), 6 front hot-swap 3.5" PCIe 5.0 x4 NVMe* drive bay(s) M.2 : 2 M.2 PCIe 4.0 x2 NVMe slot(s)</p>
<p>Chipset</p> <p>Chipset Intel® C741</p>	<p>Power Supply</p> <p>Power Supply 2x 1200W Redundant Titanium Level (96%) Hot-plug power supplies</p>
<p>System Memory</p> <p>Memory Capacity Up to 4TB 3DS ECC RDIMM, DDR5-5600MT/s(1DPC) in 16 DIMM slots</p>	<p>Cooling System</p> <p>3 Heavy Duty 8cm Fan(s)</p>
<p>Expansion Slot</p> <p>PCI-Express 4 PCIe 5.0 x16 (in x16) LP slot(s) 2 PCIe 5.0 x8 (in x8) LP slot(s)</p>	<p>Form Factor</p> <p>Form Factor 2U Rackmount</p>
<p>Integrated Onboard:</p> <p>RAID support HW RAID support via Broadcom® 3916</p> <p>Network Connectivity 2 RJ45 10GbE with Broadcom® BCM57416</p>	<p>Dimensions</p> <p>Dimensions Height : 3.5" (89mm), Width : 17.2" (437mm), Depth : 25.6" (650mm)</p>
<p>Add-on Options</p> <p>Optical Drive None</p>	<p>Email : Info@tyronesystems.com For more/current product information, Visit www.tyronesystems.com</p>

• Intel, the Intel logo, the Intel Inside logo, Xeon, and Intel Xeon Phi are trademarks of Intel Corporation in the U.S. and/or other countries.
 • Specifications subject to change without notice. Picture used for representation purpose only and the actual product may differ in looks. All other brands and names are the properties of their respective owners.