

Tyrone Camarero Specifications

Tyrone[®]

Camarero SS00TR-32

Key features

- Single socket H4 (LGA 1151) supports Intel® 7th/6th Gen. Core™ i3/i5/i7 series, Intel® Xeon® processor E3-1200 v6/v5
- Intel® C232 chipset
- Up to 64GB Unbuffered non-ECC UDIMM DDR4 2400MHz; 4 DIMM slots
- 1 PCI-E 3.0 x16, 2 PCI-E 3.0 x1, M.2 Form Factor: 2242
- Single GbE LAN with Intel® i219V
- 5 SATA3 (6Gbps) via C232; RAID 0, 1, 5, 10
- 5.1 HD Audio, TPM Header, 1 COM, 6 USB 3.0 (4 rear, 2 via header)
- Rich Front I/O: 2 USB 3.0, 2 USB 2.0, Headphone jacks
- Security: Chassis Intrusion sensor and Kensington Lock Support
- Easy Access: Tool-less side panel, PCI-E card, and HDD installations
- 2 x 5.25" drive bay, 2 x 3.5" fixed drive bay, 1 x 2.5" fixed drive bay
- 1 x 80mm Rear fan(s)
- PS2/ATX 260W/300W Multi-output power supply 80Plus Bronze, with 24pin Cable



Processor/Cache		Front Panel	
Processor	Single socket H4 (LGA 1151) supports Intel® 7th/6th Gen. Core™ i3/i5/i7 series, Intel® Xeon® processor E3-1200 v6/v5	LED Indicators	1 Network Activity LEDs, HDD activity LED, Power LED
Chipset		Buttons	Power On/Off button
Chipset	Intel® C232 chipset	Drive Bays	
System Memory		HDD Bays	2 x 5.25" drive bay, 2 x 3.5" fixed drive bay, 1 x 2.5" fixed drive bay
Memory Capacity	4x 288-pin DDR4 DIMM slots, Up to 64GB DDR4 Non-ECC UDIMM	Power Supply	
Expansion Slots		PS2/ATX 260W/300W Multi-output power supply 80Plus Bronze, with 24pin Cable	
PCI-Express	1 PCI-E 3.0 x16, 2 PCI-E 3.0 x1, M.2 Form Factor: 2242	Cooling System	
Integrated On-Board		1 x 80mm Rear fan(s)	
SATA	SATA3 (6Gbps) via C232 controller RAID 0, 1, 5, 10 support	Form Factor	
LAN	1 RJ45 Gigabit Ethernet LAN port	Form Factor	Mini-tower
Add-on Options		Height	: 14.65" (372 mm),
Raid Card	Optional	Width	: 6.89" (175 mm),
Optical Drive	Optional	Depth	: 16.85" (428 mm)
		Email : info@tyronesystems.com	
		For more/current product information, visit www.tyronesystems.com	