

Tyrone Camarero Specifications


Tyrone[®]

Camarero SS100T3R-48



Key features

- Intel® Core™ i7 / i7 Extreme Edition, and Intel® Xeon® 5600/5500/3600/3500 series (QPI up to 6.4 GT/s)
- Up to 24GB DDR3 1600/1333/1066/800 ECC / non-ECC Un-Buffered DIMM
- 2 (x16) PCI-Express 2.0, 1 (x4) PCI-Express (using x8 slot), 1x 32-bit PCI Slots
- Intel® Dual 82574L Gigabit Ethernet Controller
- Supports nVidia® SLI™ and ATI® CrossfireX™ Technology
- 8 x 3.5" hot-swap SATA Drive Bays
- 865W Low-Noise High Efficiency Cooling-Redundant Power Supply
- Tower or Rackmount
- PWM Fan Speed Control



Processor/Cache	
Processor	Intel® Core™ i7 / i7 Extreme Edition, and Intel® Xeon® 5600/5500/3600/3500 series (QPI up to 6.4 GT/s)
System Memory	
Supports up to 24 GB 1600 / 1333 / 1066 / 800MHz DDR3 ECC / non-ECC Un-Buffered memory Three Channel memory bus 6 DIMM sockets	
Expansion Slots	
PCI-Express	2 (x16) PCI-Express 2.0, 1 (x4) PCI-Express (using x8 slot), 1x 32-bit PCI Slots
Integrated On-Board	
SATA	Intel ICH10R SATA 3.0Gbps Controller RAID 0, 1, 5, 10 support
LAN	2x RJ45 LAN ports
Add-on Options	
Raid card	Optional
Optical Drive	Optional
Front Panel	
LED Indicators	Power LED Hard drive activity LED 2x Network activity LEDs System
Buttons	Power On/Off button System Reset button

Drive bays	
HDD bays	6x SATA Hot-swap Drives 2x Spare Trays
Peripheral Bays	2x 5.25" Peripheral Drive Bay 1x 5.25" Bay For Floppy Drive
Power Supply	
865W Low-Noise High Efficiency Cooling-Redundant Power Supply	
Cooling System	
2x 8cm Hot-swappable PWM Cooling Fans 1x 9cm Hot-Swappable Rear Exhaust PWM Fan 1x Active heatsink w/ heatpipe	
Form Factor	
4U Rackmountable / Tower	
Width- 17.2" (437mm), Height- 7.0" (178mm) , Depth – 25.5" (648mm)	
<p>Email : info@tyronesystems.com</p> <p>For more/current product information, visit</p> <p>www.tyronesystems.com</p>	