Tyrone Camarero Specifications

Tyrone®

Camerero   SS200T3G-13-2090

Key features

- Single socket R (LGA 2011) supports Intel® Xeon® processor E5-2600
- Up to 256GB DDR3 1600MHz reg. ECC DIMM
- 2x M2090 GPU cards pre-installed, 1 (x8) PCI-E 3.0 low-profile slot
- Integrated IPMI 2.0 with KVM and Dedicated LAN
- Intel® i350 Dual-Port GbE Controller
- 3x Hot-swap 3.5" Drive Bays
- 1400W High-efficiency Power Supply 80Plus Platinum Level (94%+) Digital Switching Control & PMBus 1.2
- 8x Counter rotating fans w/ optimal fan speed control
- Smart server management tools

intel® inside™ Xeon®

Processor/Cache

Processor	Intel® Xeon® processor E5-2600

Chipset

Intel® C602 Chipset

System Memory

Memory Capacity	8x 240-pin DDR3 DIMM sockets Supports up to 256 GB DDR3 ECC

Expansion Slots

PCI-Express	2 (x16) PCI-E 3.0 slots (2x NVIDIA Tesla M2090 Fermi GPU cards integrated) 1 (x8) PCI-E 3.0 slot for I.B. Card

Integrated On-Board

SATA	Intel ICH10R SATA 3.0Gbps Controller RAID 0, 1, 5, 10 support
LAN	2 RJ45 Gigabit Ethernet LAN ports 1 RJ45 Dedicated IPMI LAN port

Add-on Options

RAID Card	Optional
Optical Drive	None

Front Panel :

LED Indicators	Power LED HDD activity LED 2x Network activity LEDs System Overheat LED / Fan fail LED /Universal Information (UID) LED
Switches	Power On/Off Button,System Reset Button

Drive bays

HDD bays	3x 3.5" Hot-swap drive bays

Power Supply

1400W High-efficiency Power Supply 80Plus Platinum Level (94%+) Digital Switching Control & PMBus 1.2

Cooling System

8x counter-rotating fans with optimal fan speed control

Form Factor

1U Rackmount

E : info@tyronesystems.com

For more/current product information, visit

www.tyronesystems.com