

Tyrone Camarero Specifications



Camarero SS200T3R-18

Key features

- Single socket R (LGA 2011) supports Intel® Xeon® processor E5-2600 and E5-2600/1600 v2 family
- Intel® C602 Chipset
- 8x 2.5" Hot-swap drive bays
- Up to 512GB ECC DDR3, up to 1866MHz; 8x DIMM sockets
- 1x PCI-E 3.0 x16 FH expansion slot
- Intel® i350 Dual Port Gigabit
- Integrated IPMI 2.0 and KVM with Dedicated LAN
- SATA2 w/ RAID 0, 1, 10 (R5 option)
- 330W Gold Level Power Supply
- SATA Disk-on-module (DOM) power connector; TPM 1.2 and USB Type A



Processor/Cache

Processor Single socket R (LGA 2011) supports Intel® Xeon® processor E5-2600 and E5-2600/1600 v2 family

Chipset

Intel® C602 Chipset

System Memory

8x 240-pin DDR3 DIMM sockets Up to 512GB DDR3 ECC LRDIMM, Up to 256GB DDR3 ECC Registered memory (RDIMM)

Expansion Slots

PCI-Express 1x PCI-E 3.0 x16 Full-height slot

Integrated On-Board

SATA 2 SATA3 (6Gbps) & 4 SATA2 (3Gbps) RAID 0, 1, 5, 10 support RAID 0, 1, 10 support

LAN 2x RJ45 LAN ports, 1x RJ45 Dedicated IPMI LAN port

Add-on Options

RAID card optional

Optical Drive None

Front Panel

LED Indicators Power LED, Hard drive activity LED, 2x Network activity LEDs, System Overheat LED, Universal Information (UID) LED
Buttons Power On/Off Button, System Reset Button

Drive bays

HDD bays 8x 2.5" Hot-swap drive bays
Peripheral Bays None

Power Supply

330W Gold Level Power Supply

Cooling System

3x 40x28mm 4-pin PWM Cooling Fans

Form Factor

1U Rackmount
Height 1.7" (43mm), Width 17.2" (437mm), Depth 19.98" (507mm)

Email : info@tyronesystems.com

For more/current product information, visit
www.tyronesystems.com