

Tyrone Camarero Specifications



Camarero SS200T3R-34

Key features

- Single socket H2 (LGA 1155) supports Intel® Xeon® E3-1200 & v2 series, 2nd Gen Core i3 processors*
- Up to 32GB DDR3 ECC 1333MHz / 1600MHz* UDIMMs in 4 sockets
- 2 PCI-E 3.0* x8 and 1 PCI-E 2.0 x4 in x8 Expansion Slots
- Intel® 82579LM and 82574L, 2x Gigabit Ethernet LAN ports
- 9x USB 2.0 ports (2 rear + 6 via header + 1 Type-A)
- 2x 5.25" external drive bays, 4x 3.5" internal drive bays, 1x 3.5" external drive bay (OEM), 90° rotating hard drive cage
- 300W High efficiency power supply



Processor/Cache	
Processor	Single socket H2 (LGA 1155) supports Intel® Xeon® E3-1200 & v2 series, 2nd Gen Core i3 processors*
Chipset	
	Intel® C202 PCH chipset
System Memory	
Memory Capacity	4x 240-pin DDR3 DIMM sockets Supports up to 32 GB DDR3 ECC Un-Buffered memory (UDIMM)
Expansion Slots	
PCI-Express	2 PCI-E 3.0* x8 slots 1 PCI-E 2.0 x4 in x8 slot
Integrated On-Board	
SATA	6x SATA 2.0 (3Gbps) w/ RAID 0, 1, 5,10
LAN	2x RJ45 LAN ports
Add-on Options	
RAID Card	Optional
Optical Drive	None

Front Panel :	
LED Indicators	Power LED Hard drive activity LED Network activity LED System Overheat LED
Switches	Power On/Off Button, System Reset Button
Drive bays	
HDD bays	4x 3.5" tool-less HDD trays Enterprise SATA HDD only recommended. 2x 5.25" external drive bays 1x 3.5" external drive bay (OEM option)
Power Supply	
	300W High efficiency power supply
Cooling System	
	1x 9cm (rear) PWM fan w/ tool-less design 1x 8cm (front) cooling fan (optional) Optimized Cooling Technology at 25dB Whisper-Quiet Operation
Form Factor	
	Mid-Tower
Height	14.25" (362 mm)
Width	7.25" (184 mm)
Depth	16.75" (425 mm)
<p>Email : info@tyronesystems.com</p> <p>For more/current product information, visit www.tyronesystems.com</p>	