

Tyrone Camarero Specifications

Tyrone[®]

Camarero SS300TR-14

Key features

- Single socket R3 (LGA 2011) supports Intel® Xeon® processor E5-2600 v4/ v3 family
- Intel® C612 chipset
- 4x 3.5" Hot-swap SATA3 drive bays
- Up to 1TB ECC 3DS LRDIMM , up to DDR4- 2400MHz ; 8x DIMM slots Mini-PCIe w/ mSATA support
- 1x PCI-E 3.0 x16 slot
- Intel® i350-AM2 Dual port GbE LAN
- Integrated IPMI 2.0 and KVM with Dedicated LAN
- I/O ports: 1x VGA, 1x COM, 2x USB 3.0, 4x USB 2.0
- 350W Gold Level Power Supply



Processor/Cache	
Processor	Single socket R3 (LGA 2011) supports Intel® Xeon® processor E5-2600 v4/ v3 family
Chipset	
Chipset	Intel® C612 chipset
System Memory	
Memory Capacity	8x 288-pin DDR4 DIMM slots, Up to 1TB ECC 3DS LRDIMM, Up to 512GB ECC LRDIMM, Up to 256GB ECC RDIMM
Expansion Slots	
PCI-Express	1x PCI-E 3.0 x16 slot
Integrated On-Board	
SATA	SATA3 (6Gbps) via C612 controller, RAID 0, 1, 10 support
LAN	2x RJ45 Gigabit Ethernet LAN ports, 1x RJ45 Dedicated IPMI LAN port
Add-on Options	
Raid	Optional
Optical Drive	Optional

Front Panel	
LED Indicators	Power LED, Hard drive activity LED, 2x Network activity LEDs, System Overheat LED
Buttons	Power On/Off button, System Reset button
Drive Bays	
HDD bays	4x 3.5" Hot-swap drive bays, 2x 2.5" Fixed drives internal
Power Supply	
350W Gold Level Power Supply	
Cooling System	
4x 40x28mm 4-pin PWM Cooling Fans	
Form Factor	
Form Factor	1U Rackmount
Height	: 1.7" (43mm),
Width	: 17.2" (437mm),
Depth	: 19.8" (503mm)
<p>Email : info@tyronesystems.com</p> <p>For more/current product information, visit</p> <p>www.tyronesystems.com</p>	