

Tyrone Camarero Specifications

Tyrone®

Camarero SS300TS-34

Key features

- Single socket R3 (LGA 2011) supports Intel® Core i7 series, Xeon® processor E5-2600 v4/ v3 and E5-1600 v4/v3 family
- Intel® X99 chipset
- Up to 128GB non-ECC UDIMM DDR4, frequency up to 3300MHz (OC); 8x DIMM slots
- 4 PCI-E 3.0 x16 (run at 16/16/NA/8 or 16/8/8/8), 2 PCI-E 2.0 x1 (in x4)
- Intel® i210-AT Dual port GbE LAN
- 10x SATA3 (6Gbps)
- 1x COM, 1x TPM, 8x USB 3.0 ports (6 rear + 2 via header)
- HD Audio 7.1 channel connector by Realtek ALC1150
- Supports 2/3/4-Ways NVIDIA SLi
- 4 x 3.5" fixed drive bay, Optional 4 x 2.5" fixed drive bay
- PS2/ATX 900W multiple outputs power supply, Gold level, 12cm fan



Processor/Cache

Processor	Single socket R3 (LGA 2011) supports Intel® Core i7 series, Xeon® processor E5-2600 v4/ v3 and E5-1600 v4/v3 family
-----------	---

Chipset

Chipset	Intel® X99 chipset
---------	--------------------

System Memory

Memory Capacity	8x 288-pin DDR4 DIMM slots, Supports up to 128GB DDR4 Non-ECC Un-Buffered memory (UDIMM) in 8 DIMM slots
-----------------	--

Expansion Slots

PCI-Express	4 PCI-E 3.0 x16 (run at 16/16/NA/8 or 16/8/8/8), 2 PCI-E 2.0 x1 (in x4)
-------------	---

Integrated On-Board

SATA	SATA3 (6Gbps) via Intel X99 controller, 10x SATA3 ports: 6x iSATA (RAID 0, 1, 5, 10) and 4x SATA
LAN	2x RJ45 Gigabit Ethernet LAN ports

Add-on Options

Raid Card	Optional
Optical Drive	Optional

Front Panel

LED Indicators	1 Network Activity LEDs, HDD activity LED, System Information LED
----------------	---

Buttons	Power On/Off button
---------	---------------------

Drive Bays

HDD Bays	4 x 3.5" fixed drive bay. Optional 4 x 2.5" fixed drive bay
----------	--

Peripheral Bays	2 x standard 5.25" drive bay, 1 x card reader module
-----------------	---

Power Supply

PS2/ATX 900W multiple outputs power supply, Gold level, 12cm fan
--

Cooling System

1 x 12cm rear exhaust fan(s), Optional 1 x 12cm (front) cooling fan
--

Form Factor

Form Factor	Mid-tower
Height	: 16.7"(424 mm),
Width	: 7.6" (193 mm),
Depth	: 20.68"(525 mm)

Email : info@tyronesystems.com

**For more/current product information, visit
www.tyronesystems.com**