# **Tyrone Camarero Specifications**

# Tyrone

# Camarero SS400TG-13T

## **Key features**

Edge Computing, Micro Data Center, AI/ML, Deep Learning Training and Inference Virtualization, Cloud Computing, 1U Single Processor (Intel) 2 GPU System

- 2nd Generation Intel® Xeon® Scalable Processors (Cascade Lake-SP), Intel® Xeon® Scalable Processors., Single Socket P (LGA 3647) supported, CPU TDP support 205W
- Intel® C621 chipset
- Up to 1.5TB 3DS ECC RDIMM, DDR4-2933MHz; Up to 1.5TB 3DS ECC LRDIMM, DDR4-2933MHz, in 6 DIMM slots
- 2 PCI-E 3.0 x16 slots (support double-width GPU), 1 PCI-E 3.0 x16 low-profile slot (center left)
- . 3 Hot-swap 3.5" SAS/SATA drive bays, 1 slim DVD-ROM drive bay
- 2x 10GBase-T LAN ports via Intel X550
- Dual M.2 in 2280
- 8 Heavy duty 4cm counter-rotating 4cm fans with air shroud & optimal fan speed control
- 1400W High-efficiency Power Supply Platinum Level (94%+)







#### Processor/Cache

2nd Generation Intel® Xeon® Scalable

Processors (Cascade Lake-SP), Intel® Xeon® Scalable Processors., Single Socket P (LGA 3647) supported,

CPU TDP support 205W

Chipset

Chipset Intel® C621 chipset

### System Memory

Memory Capacity Up to 1.5TB 3DS ECC RDIMM, DDR4-2933

MHz; Up to 1.5TB 3DS ECC LRDIMM, DDR4-2933MHz, in 6 DIMM slots

# **Expansion Slots**

PCI-Express 1 PCI-E 3.0 x16 slot (center right),

1 PCI-E 3.0 x16 slot (right riser), 1 PCI-E 3.0 x16 slot (left riser)

### Integrated On-Board

SATA SATA3 (6Gbps) with RAID 0, 1, 5, 10

LAN 2 RJ45 10GBase-T ports,

1 RJ45 Dedicated IPMI LAN port

#### **Add-on Options**

Raid Card Optional
Optical Drive Optional

#### Front Panel

LED Indicators Power LED, Hard drive activity LED,

Network activity LEDs System Overheat

LED / Fan fail LED / UID LED

Buttons Power On/Off button,

System Reset button

#### **Drive Bays**

HDD Bays 3 Hot-swap 3.5" SAS/SATA drive bays

M.2 Dual M.2 Mini PCle support 2280

Peripheral Bays 1 slim DVD-ROM drive bay or 1 USB +

COM port tray

### **Power Supply**

1400W High-efficiency Power Supply Platinum Level (94%+)

# Cooling System

8 Heavy duty 4cm counter-rotating 4cm fans with air shroud & optimal fan speed control

#### **Form Factor**

Form Factor 1U Rackmount

Height : 1.7\* (43mm), Width : 17.2" (437mm), Depth : 28.2" (716mm)

Email: info@tyronesystems.com

For more/current product information, visit

www.tyronesystems.com

Intel, the Intel logo, the Intel Inside logo, Xeon, and Intel Xeon Phi are trademarks of Intel Corporation in the U.S and/Or other Countries

Specifications subject to change without notice. Picture used for representation purpose only and the actual product may differ in looks. All other brands and names are the property of their respective owners