Tyrone Camarero Specifications

Camarero SS400TR-12

Key features

- Single socket H4 (LGA 1151) supports Intel® Xeon® processor E3-1200 v6/v5, Intel® 7th/6th Gen. Core™ i3 series,Intel® Celeron® and Intel® Pentium®
- Intel® C236 chipset
- . Up to 64GB Unbuffered ECC UDIMM DDR4 2400MHz; 4 DIMM slots
- 1 PCI-E 3.0 x8 (in x16), 1 PCI-E 3.0 x8, 1 PCI-E 3.0 x4 (in x8)
- . Dual GbE LAN with Intel® i210-AT
- 8x SATA3 (6Gbps) via C236; RAID 0, 1, 5, 10
- I/O: 1x VGA, 2x COM, TPM 1.2 header
- · 2x SuperDOM with built-in power
- 5x USB 3.0 (2 rear + 2 via header + 1 Type A), 6x USB 2.0 (2 rear + 4 via headers)
- M.2 NGFF connector
- · Support Intel VHD with selected CPU
- · 2x 3.5" Internal Drive Bays
- 1x Slim DVD-ROM Drive (optional)
- 2x Counter-rotating Fans
- 350W High-efficiency Power Supply Gold Level Certified









Processor/Cache

Processor Single socket H4 (LGA 1151) supports

Intel® Xeon® processor E3-1200 v6/v5, Intel® 7th/6th Gen. Core™ i3 series, Intel® Celeron® and Intel® Pentium®

Chipset

Chipset Intel® C236 chipset

System Memory

Memory Capacity Up to 64GB Unbuffered ECC UDIMM

DDR4 2400MHz; 4 DIMM slots

Expansion Slots

PCI Express 1x PCI-E 3.0 x8 (in x16) slot,

1x PCI-E 3.0 x8 slot, 1x PCI-E 3.0 x4 (in x8) slot

Integrated On-Board

SATA SATA3 (6Gbps) via C236 controller,

RAID 0, 1, 5, 10 support

LAN 2x RJ45 Gigabit Ethernet LAN ports,

1x RJ45 Dedicated IPMI LAN port

Add-on Options

Raid Card Optional

Optical Drive Optional

Front Panel

Front Panel Power LED, Hard drive activity LED,

2x Network activity LEDs, System Overheat LED

Buttons Power On/Off button. Reset button

Drive Bays

HDD Bays (Internal) 2x 3.5" Internal Drive Bays,

SAS or enterprise SATA HDD only

recommended

Peripheral Bays Slim DVD-ROM Drive (optional)

Power Supply

350W High-efficiency Power Supply Gold Level Certified

Cooling System

2x 4cm 4-pin PWM Fans

Form Factor

Form Factor 1U Rackmount

Height: 1.7" (43mm), Width: 17.2" (437mm), Depth: 14.5" (369mm)

Email: info@tyronesystems.com For more/current product information, visit

www.tyronesystems.com

O Intel, the Intel logo, the Intel Inside logo, Xeon, and Intel Xeon Phi are trademarks of intel Corporation in the U.S and/Or other Countries

Specifications subject to change without notice. Picture used for representation purpose only and the actual product may differ in looks. All other brands and names are the property of their respective owners