

Tyrone Camarero Specifications

Camarero SS400TR-34L-1585

Key features

- Intel® Xeon® processor E3-1585 v5, Single socket FCBGA 1440, 4-Core, 8 Threads, 65W
- Intel® C236 chipset
- Up to 64GB ECC Unbuffered SO-DIMM, DDR4 2133MHz; 4 DIMM slots
- Support Intel® Iris Pro Graphics P580 (GT4e) , for VHD and Quick Sync Video
- 1 PCI-E 3.0 x8 (in x16 slot), 1 PCI-E 3.0 x8, 1 PCI-E 3.0 x4 (in x8 slot)
- 6 SATA3 (6Gbps) via C236; RAID 0, 1, 5, 10
- 2 SuperDOM with built-in power
- 5 USB 3.0 (2 rear, 1 Type A, 2 internal)
- M.2 NGFF connector, M.2 Interface: PCI-E 3.0 x4 and SATA, Form Factor: 2242, 2280, 22110, Key: M-Key, Double Height Connector
- 2 x 5.25" drive bay, 4 x 3.5" fixed drive bay
- 1 x 9cm (2050 RPM) rear exhaust fan(s), Optional 1 x 8cm (front) cooling fan
- 300W Bronze Level Certified High-Efficiency Power Supply

Tyrone®



Processor/Cache

Processor	Intel® Xeon® processor E3-1585 v5, Single socket FCBGA 1440, 4-Core, 8 Threads, 65W
-----------	---

Chipset

Chipset	Intel® C236 chipset
---------	---------------------

System Memory

Memory Capacity	Up to 64GB ECC Unbuffered SO-DIMM, DDR4 2133MHz; 4 DIMM slots
-----------------	---

Expansion Slots

PCI-Express	1 PCI-E 3.0 x8 (in x16 slot), 1 PCI-E 3.0 x8, 1 PCI-E 3.0 x4 (in x8 slot)
-------------	---

Integrated On-Board

SATA	Intel® C236 controller for 6 SATA3 (6 Gbps) ports; RAID 0, 1, 5, 10
------	---

Add-on Options

Raid Card	Optional
Optical Drive	None

Front Panel

LED	1 Network Activity LEDs, HDD activity LED, Power LED, System Overheat LED
Buttons	Power On/Off button

Drive Bays

Drive Bays	2 x 5.25" drive bay, 4 x 3.5" fixed drive bay
------------	---

Power Supply

300W Bronze Level Certified High-Efficiency Power Supply

Cooling System

1 x 9cm (2050 RPM) rear exhaust fan(s),
Optional 1 x 8cm (front) cooling fan

Form Factor

Form Factor	Mini Tower
Height:	14.25" (362 mm),
Width:	7.25" (184 mm),
Depth:	16.75" (425 mm)

Email : info@tyronesystems.com

For more/current product information, visit

www.tyronesystems.com