Tyrone Camarero Specifications

Camarero SS400TW-14RT

Key features

- DB Processing & Storage, Data Center Applications, Firewall Applications
- 2nd Generation Intel® Xeon® Scalable Processors (Cascade Lake-SP), Intel® Xeon® Scalable Processors., Single Socket P (LGA 3647) supported, CPU TDP support 205W
- Intel *C622 chipset
- Up to 1.5TB 3DS ECC RDIMM, DDR4-2933MHz; Up to 1.5TB 3DS ECC LRDIMM, DDR4-2933MHz, in 6 DIMM slots
- 2 PCI-E 3.0 x16 (FHFL) slots, 1 PCI-E 3.0 x8 (LP) slot
- · 4 Hot-swap 3.5" SATA3 drive bays
- 2x 10GBase-T ports with Intel X772 + X557
- 1 VGA, 2 COM, 2 USB 3.0, 2 USB 2.0
- 2 SuperDOM (Disk on Module) ports
- 500W Redundant power supplies Platinum Level Certified









| | | | | | _ | |
|---|---|--------|-----|------|---|----|
| | - | \sim | SSO | | ~ | 20 |
| - | | - | | | | - |
| | | | | | | |

Processor 2nd Generation Intel® Xeon® Scalable

Processors (Cascade Lake-SP), Intel® Xeon® Scalable Processors., Single Socket P (LGA 3647) supported,

CPU TDP support 205W

Chipset

Chipset Intel *C622 chipset

System Memory

Memory Capacity Up to 1.5TB 3DS ECC RDIMM,

DDR4-2933MHz; Up to 1.5TB 3DS ECC LRDIMM, DDR4-2933MHz, in 6 DIMM

slots

Expansion Slots

PCI Express 2 PCI-E 3.0 x16 (FHFL) slots,

1 PCI-E 3.0 x8 (LP) slot

Integrated On-Board

SATA SATA3 (6Gbps); RAID 0, 1, 5, 10

LAN 2 RJ45 10GBase-T LAN ports,

1 RJ45 dedicated IPMI LAN port

Add-on Options

Raid Optional Optical Drive None Front Panel

LED Power LED, Hard drive activity LED,

Network activity LEDs, System Overheat LED,

Information LED

Buttons Power On/Off button, System Reset button

Drive Bays

HDD Bays 4 Hot-swap 3.5" SATA3 drive bays,

M.2 mini-PCI-e support

Power Supply

500W Redundant power supplies Platinum Level Certified

Cooling System

5 Counter-rotation 40x56mm PWM fans,

1 fan for AOC cooling (option)

Form Factor

Form Factor 1U Rackmount

Width 17.2" (437mm) Height 1.7" (43mm) Depth 25.6" (650mm)

Email: info@tyronesystems.com

For more/current product information, visit

www.tyronesystems.com

Intel, the Intel logo, the Intel Inside logo, Xeon, and Intel Xeon Phi are trademarks of intel Corporation in the U.S and/Or other Countries

Specifications subject to change without notice. Picture used for representation purpose only and the actual product may differ in looks. All other brands and names are the property of their respective owners