

# Tyrone Camarero Specifications

## Camarero SS40TR-28R

### Key features

- 2nd Generation Intel® Xeon® Scalable Processors (Cascade Lake-SP), Intel® Xeon® Scalable Processors., Single Socket P (LGA 3647) supported, CPU TDP support 165W
- Intel® C621 Chipset
- Up to 2TB 3DS ECC RDIMM, DDR4-2933MHz; Up to 2TB 3DS ECC LRDIMM, DDR4-2933MHz, in 8 DIMM slots; Up to 1TB Intel Optane DC Persistent Memory in memory mode (Cascade Lake Only)
- Expansion slots: 2 PCI-E 3.0 x8 (in x16), 4 PCI-E 3.0 x8, 1 PCI-E 3.0 x4 (in x8)
- 2 GbE LAN ports
- 8 SATA3 (6Gbps) ports
- I/O: 1 VGA, 2 COM, TPM header
- 2 SuperDOM with built-in power
- 5 USB 3.0 (2 rear, 1 Type-A, 2 via header), 8 USB 2.0 (2 rear, 6 via headers)
- M.2 NGFF connector, M.2 Interface: PCI-E 3.0 x4 and SATA, Form Factor: 2280, 22110, Key: M-Key, Double Height Connector
- 8 x 3.5" hot-swap SAS/SATA drive bay with SGPIO, 2 x 3.5" fixed drive bay
- 600W/740W/800W/1000W Redundant Power supply



### Processor/Cache

Processor	2nd Generation Intel® Xeon® Scalable Processors (Cascade Lake-SP), Intel® Xeon® Scalable Processors., Single Socket P (LGA 3647) supported, CPU TDP support 165W
-----------	--

### Chipset

Chipset	Intel® C621 Chipset
---------	---------------------

### System Memory

Memory Capacity	Up to 2TB 3DS ECC RDIMM, DDR4-2933MHz; Up to 2TB 3DS ECC LRDIMM, DDR4-2933MHz, in 8 DIMM slots; Up to 1TB Intel Optane DC Persistent Memory in memory mode (Cascade Lake Only)
-----------------	--

### Expansion Slots

PCI Express	2 PCI-E 3.0 x8 (in x16), 4 PCI-E 3.0 x8, 1 PCI-E 3.0 x4 (in x8)
-------------	---

### Integrated On-Board

SATA	Intel® C621 controller for 8 SATA3 (6 Gbps) ports; RAID 0,1,5,10
LAN	2 RJ45 Gigabit Ethernet LAN ports

### Add-on Options

Raid Card	Optional
Optical Drive	Optional

### Front Panel

LED	2 Network Activity LEDs, HDD activity LED, Power Status LED, System Information LED
Buttons	Power On/Off button, System Reset Button

### Drive Bays

HDD Bays	8 x 3.5" hot-swap SAS/SATA drive bay with SGPIO, 2 x 3.5" fixed drive bay
Peripheral Bays	Optional 1 x slim DVD-ROM drive bay, Optional 2 x USB 2.0 ports, Optional 1 x COM port tray, Optional 2 x USB 3.0 ports

### Power Supply

600W/740W/800W/1000W Redundant Power supply

### Cooling System

3 x 8cm (7000 RPM) hot-swap PWM cooling fan(s)

### Form Factor

Form Factor	2U Rackmount
Height	3.5" (89 mm),
Width	17.2" (437 mm),
Depth	25.5" (647 mm)

Email : [info@tyronesystems.com](mailto:info@tyronesystems.com)

For more/current product information, visit  
[www.tyronesystems.com](http://www.tyronesystems.com)