

# Tyrone Camarero Specifications

Camarero SS4C0TA-45R

## Key features

- Intel® 8th/9th Generation Core i9/Core i7/Core i5/Core i3/Pentium®/Celeron® series Processor, Intel® Xeon® E-2100 Processor, Intel® Xeon® E-2200 Processor, Single Socket LGA-1151 (Socket H4) supported, CPU TDP support Up to 95W TDP
- Intel® C246
- Up to 128GB Unbuffered ECC/non-ECC UDIMM, DDR4-2666MHz, in 4 DIMM slots
- 1 PCI-E 3.0 x4, 1 PCI-E 3.0 x1, 2 PCI-Ex16 slots are running at NA/16, or 8/8, 1 - 5V PCI 32bit, M.2 Interface: 2 PCI-E 3.0 x4, M.2 Form Factor: 2242/2260/2280/22110, M.2 Key: M-Key, M.2#1 are shared with PCI-Ex4 slot, M.2#2 is shared with U.2, U.2 Interface: 1 PCI-E 3.0 x4
- 1 HDMI port, 1 DVI - D port, 1 DP (DisplayPort) port, Intel UHD P630 graphic
- (For CPU Xeon E-21XXG series only)
- Intel® C246 controller for 8 SATA3 (6 Gbps) ports; RAID 0,1,5,10
- Single LAN with Intel® Ethernet Controller I210-AT, Single LAN with Intel® PHY I219LM LAN controller, Support vPro
- 5 x 3.5" hot-swap SAS3/SATA drive bay
- 1 x 9cm hot-swap cooling fan(s), 2 x 8cm hot-swap exhaust fan(s) & air shroud
- 800W Redundant Power Supplies Platinum Level (94%)

# Tyrone®



## Processor/Cache

Processor	Intel® 8th/9th Generation Core i9/Core i7/Core i5/Core i3/Pentium®/Celeron® series Processor, Intel® Xeon® E-2100 Processor, Intel® Xeon® E-2200 Processor, Single Socket LGA-1151 (Socket H4) supported, CPU TDP support Up to 95W TDP
-----------	---

## Chipset

Chipset	Intel® C246
---------	-------------

## System Memory

Memory Capacity	Up to 128GB Unbuffered ECC/non-ECC UDIMM, DDR4-2666MHz, in 4 DIMM slots
-----------------	---

## Expansion Slots

PCI-Express	1 PCI-E 3.0 x4, 1 PCI-E 3.0 x1, 2 PCI-Ex16 slots are running at NA/16, or 8/8, 1 - 5V PCI 32bit, M.2 Interface: 2 PCI-E 3.0 x4, M.2 Form Factor: 2242/2260/2280/22110, M.2 Key: M-Key, M.2#1 are shared with PCI-Ex4 slot, M.2#2 is shared with U.2, U.2 Interface: 1 PCI-E 3.0 x4
-------------	--

## Integrated On-Board

SATA	Intel® C246 controller for 8 SATA3 (6 Gbps) ports; RAID 0,1,5,10
LAN	2 1GbE LAN ports

## Add-on Options

Raid Card	Optional
Optical Drive	Optional

## Front Panel

LED	2 Network Activity LEDs, Fan Fail/System Over Heat LED, HDD activity LED, Power Status LED
Buttons	Power On/Off button, System Reset Button

## Drive Bays

HDD Drives	5 x 3.5" hot-swap SAS3/SATA drive bay
Peripheral Drives	3 x standard 5.25" drive bay

## Power Supply

800W Redundant Power Supplies Platinum Level (94%)
--

## Cooling System

1 x 9cm hot-swap cooling fan(s), 2 x 8cm hot-swap exhaust fan(s) & air shroud
--

## Form Factor

Form Factor	4U Rackmount
Height :	7" (178 mm),
Width :	17.2" (437 mm),
Depth :	20.5" (521 mm)

Email : [info@tyronesystems.com](mailto:info@tyronesystems.com)

For more/current product information, visit

[www.tyronesystems.com](http://www.tyronesystems.com)