

# Tyrone Camarero Specifications

Tyrone

## Camarero: SSA200A3A-48

### Key Feature

- AMD EPYC™ 9004 series Processors, Single Socket SP5 supported, CPU TDP supports Up to 400W TDP
- System on Chip
- 12 DIMM slots, Up to 3TB 3DS ECC Registered RDIMM, DDR5-4800MHz
- 3 PCIe 5.0 x16 (in x16 slot),2 PCIe 5.0 x8
- Up to 6 USB 3.0 ports(4 rear + 2 via header)
- 8 SATA3
- 6 PWM 4-pin Fans with tachometer status monitoring
- M.2 Interface: 2 PCIe 4.0 x4 M.2 Form Factor: 2280, 22110
- Support 8 x 3.5"/2.5"(SAS/SATA) Hot Swappable Bays, 2 x 5.25"ODD + 1 x Slim ODD
- Cabinet with 3 x 2500 Mid Fan, 1 x Rear Fan
- Support 1200W/1600W/2000W Power Supply



Processor/Cache		Integrated Onboard	
Processor	AMD EPYC™ 9004 series Processors, Single Socket SP5 supported, CPU TDP supports Up to 400W TDP	SATA	8 SATA3 (6Gbps) port(s)
Chipset		Network Connectivity	Dual LAN with Broadcom BCM5720 1GBase-T
Chipset	System on Chip	Drive bays	
System Memory		HDD Bays	Support 8 x 3.5"/2.5"(SAS/SATA) Hot Swappable Bays, 2 x 5.25"ODD + 1 x Slim ODD
Memory Capacity	12 DIMM slots, Up to 3TB 3DS ECC Registered RDIMM, DDR5-4800MHz	Power Supply	
Expansion Slot		Power Supply	Support 1200W/1600W/2000W Power Supply
PCI-Express	3 PCIe 5.0 x16 (in x16 slot),2 PCIe 5.0 x8	Cooling System	
Add-on Options		Form Factor	
Raid Card	Optional	Form Factor	4U Rackmount
Optical Drive	None	Email : <a href="mailto:Info@tyronesystems.com">Info@tyronesystems.com</a>	
		For more/current product information, Visit <a href="http://www.tyronesystems.com">www.tyronesystems.com</a>	

◦ AMD the AMD logo inside are trademarks of Advanced Micro Devices in US and / Or other Countries  
◦ Specifications subject to change without notice. Picture used for representation purpose only and the actual product may differ in looks . All other brands and names are the property of their respective owners