

Tyrone Camarero Specifications

Tyrone

Camerero: SSA200C3R-212

Key Feature

- AMD EPYC™ 9004/9005* Series Processors (*AMD EPYC™ 9005 series drop-in support requires board revision 2.x)
- System on Chip
- Support up to DDR5 12 DIMM slots (1DPC), speed up to 6000 MT/s (Please check System Memory Section for detail)
- 3 PCIe 5.0 x16 ; 2 PCIe 5.0 x8
Optional : 4x PCI-E 5.0 x16
- 2x 10GBase-T LAN Ports via Broadcom BCM57416
- Up to 6 USB 3.0 ports(4 rear + 2 via header)
- 8 SATA3
- ASPEED AST2600 BMC graphics
- 6 PWM 4-pin Fans with tachometer status monitoring
- M.2 Interface: 2 PCIe 4.0 x4M.2 Form Factor: 2280, 22110
- 12 x front loaded 2.5"/3.5" bays(SAS/SATA).
- Support CRPS PSU(FSP) 800W/1200W/1600W



Processor/Cache		Front Panel	
Processor	AMD EPYC™ 9004/9005* Series Processors (*AMD EPYC™ 9005 series drop-in support requires board revision 2.x)	Front Panel	1 x Power Status,1 x HDD Activity,2 x LAN Activity,1x UID
Chipset		Drive bays	
Chipset	System on Chip	HDD Bays	12 x front loaded 2.5"/3.5" bays(SAS/SATA).
System Memory		Power Supply	
Memory Capacity	Support up to DDR5 12 DIMM slots (1DPC), speed up to 6000 MT/s (Please check System Memory Section for detail)	Power Supply	Support CRPS PSU(FSP) 800W/1200W/1600W
Expansion Slot		Dimensions	
PCI-Express	3 PCIe 5.0 x16 ; 2 PCIe 5.0 x8 Optional : 4x PCI-E 5.0 x16	Dimensions	660 x 436 x 87 mm mm (22" x 7.9" x 16.9")
Integrated Onboard:		Email : Info@tyronesystems.com For more/current product information, Visit www.tyronesystems.com	
Network Connectivity	Dual LAN with Broadcom BCM5720 1GBase-T		
LAN	1 RJ45 Dedicated IPMI LAN port, 2 RJ45 10GBase-T LAN ports		
Add-on Options			
Raid Card	Optional		
Optical Drive	None		