

Tyrone Camarero Specifications

Tyrone

Camarero: SSA200F0R-48

Key Feature

- AMD EPYC™ 9004 series Processors, Single Socket SP5 supported, CPU TDP supports Up to 400W TDP
- System on Chip
- 12 DIMM slots, Up to 3TB 3DS ECC Registered RDIMM, DDR5-4800MHz
- 3 PCIe 5.0 x16 (in x16 slot), 2 PCIe 5.0 x8
- Up to 6 USB 3.0 ports(4 rear + 2 via header)
- 8 SATA3
- 6 PWM 4-pin Fans with tachometer status monitoring
- M.2 Interface: 2 PCIe 4.0 x4 M.2 Form Factor: 2280, 22110
- Support 8 x 3.5"/2.5"(SATA)+2x 2.5"(SSD) Fix disks
- Cabinet with 3 x 2500 Mid Fan, 1 x Rear Fan
- 1200W Redundant Power Supply
- Dual LAN with Broadcom BCM5720 1GBase-T
- **Optional** : 2x 10GBase-T LAN Ports via Broadcom BCM57416



Processor/Cache	
Processor	AMD EPYC™ 9004 series Processors, Single Socket SP5 supported, CPU TDP supports Up to 400W TDP
Chipset	
Chipset	System on Chip
System Memory	
Memory Capacity	12 DIMM slots, Up to 3TB 3DS ECC Registered RDIMM, DDR5-4800MHz
Expansion Slot	
3 PCIe 5.0 x16 (in x16 slot), 2 PCIe 5.0 x8	
Integrated Onboard:	
SATA	8 SATA3 (6Gbps) port(s)
Network Controllers	Dual LAN with Broadcom BCM5720 1GBase-T Optional : 2x 10GBase-T LAN Ports via Broadcom BCM57416
Add-on Options	
Raid Card	Optional
Optical Drive	None

Drive bays	
Drive bays	Support 8 x 3.5"/2.5"(SATA)+2x 2.5"(SSD) Fix disks
Power Supply	
Power Supply	1200W Redundant Power Supply
Cooling System	
Cabinet with 3 x 2500 Mid Fan, 1 x Rear Fan	
Form Factor	
Form Factor	4U Rackmount
<p>Email : Info@tyronesystems.com</p> <p>For more/current product information, Visit www.tyronesystems.com</p>	