

Tyrone Camarero Specifications

Camarero- SSA20F0A-55

Tyrone

Key Feature

- "AMD Ryzen™ Threadripper™ PRO 7000 WX-Series and Ryzen™ Threadripper™ 7000 Series Processors Single socket sTR5, LGA-4844, Up to 350W TDP, Overclocking supported"
- AMD TRX50
- Up to 4TB of memory with speeds of 5200+MT/s (1DPC) with overclocking support, Memory addressing up to 1TB/channel is subject to AMD Infrastructure Roadmap for Socket sTR5 Processors
- M.2 Interface: 2 PCIe 4.0 x4 (RAID 0, 1), M.2 Form Factor: 2280/22110, M.2 Key: M-Socket
- 2 PCIe 5.0 x16, support 2 triple/dual/single-width GPU cards, 2 PCIe 5.0 x8, open rear
- Single LAN with ASPEED AST2600, Dedicated LAN for IPMI,
Optional: Dual LAN with 10Gb Broadcom BCM57416
- 4 SATA 3 (6Gb, RAID 0, 1, 10), 1 MCIO connector (PCIe Gen4 x8) to support 2 U.2 ports via cable for NVMe 2.5" SSD drives
- 1 USB 3.2 Gen2x2 (20G, 1 rear Type-C), 1 USB 3.2 Gen2x1 (10G, 1 header Type-C), 4 USB 3.2 Gen2x1 (4 rear Type-A), 1 USB 3.2 Gen1x1 (5Gb, 1 header Type-A 2 ports), 1 USB 2.0 (1 header Type-A 2 ports)
- 1 Dedicated LAN for IPMI
- Overclocking supported on CPU and RDIMM
- 3x Middle 8cm (9400 rpm) PWM Fans & 2x 8cm (9400 rpm) PWM Fans
- 3x 5.25" External HDD Drive Bays & 8x 3.5"/2.5" Hot-Swappable HDD Drives
- 1200W (1 + 1) Redundant Titanium Level Certified High-Efficiency Power Supply



| Processor/Cache | | Front Panel | |
|--|--|-----------------|--|
| Processor | "AMD Ryzen™ Threadripper™ PRO 7000 WX-Series and Ryzen™ Threadripper™ 7000 Series Processors Single socket sTR5, LGA-4844, Up to 350W TDP, Overclocking supported" | LED | Power status LED, HDD activity LED, System Information LED, Power Fail LED , 2 Network Activity LEDs |
| System Memory | | Buttons | Power On/Off button, System Reset button |
| Memory Capacity | Up to 4TB of memory with speeds of 5200+MT/s (1DPC) with overclocking support, Memory addressing up to 1TB/channel is subject to AMD Infrastructure Roadmap for Socket sTR5 Processors | Port | 2x USB 3.0 Port(s) |
| Chipset | | Drive bays | |
| Chipset | AMD TRX50 | HDD Bays | 8x 3.5"/2.5" hot-swap SAS drive bay with SES3 |
| Expansion Slot | | Peripheral bays | 3x standard 5.25" drive bay |
| PCI-Express | 2 PCIe 5.0 x16, support 2 triple/dual/single-width GPU cards, 2 PCIe 5.0 x8, open rear | Power Supply | |
| Integrated Onboard | | Power Supply | 1200W (1 + 1) Redundant Titanium Level Certified High-Efficiency Power Supply |
| SATA | 4 SATA3 ports; RAID 0,1,10 | Cooling System | |
| LAN | Single LAN with ASPEED AST2600, Dedicated LAN for IPMI, Optional: Dual LAN with 10Gb Broadcom BCM57416 | Fans | 2x 80mm PWM Rear Chassis Fans (9.4k RPM), 3x 80mm high-performance fan(s) (9.4k RPM) |
| Raid Card | | Form Factor | |
| Optical Drive | Optional | Form Factor | 4U Rackmount |
| | | Dimensions | |
| | | Dimensions | Dimensions : Height -17.8" (452 mm), Width - 7" (178 mm), Depth -25.5" (647 mm) |
| Email : Info@tyronesystems.com For more/current product information, Visit www.tyronesystems.com | | | |