Tyrone Camarero Specifications

Camarero SSA700TR-212RL

Key features

- Single AMD EPYC[™] 7001/7002* series Processor (*Board revision 2.x required) Socket SP3 Cores:Up to 32 Cores, Up to 64 Cores (Board revision 2.x required)
- System on Chip
- 8 DIMM slots Supports up to 1TB Registered ECC DDR4 2666MHz SDRAM in 8 DIMMs, Supports up to 2TB Registered ECC DDR4 3200MHz SDRAM (Board revision 2.x required), 8-channel memory bus
- 3 PCI-E 3.0 x8, 3 PCI-E 3.0 x16 .2:Interface: PCI-E 3.0 x4, Form factor: 2280, 22110,Key: M-key
- 16 SATA3, 1 M.2
- Dual Gigabit Ethernet LAN Ports
- ASPEED AST2500 BMC graphics
- Up to 5 USB 3.0 ports, 2 rear + 2 via header + 1 Type A), Up to 4 USB 2.0 ports, (2 rear + 2 via header)
- 7 PWM 4-pin Fans with tachometer status monitoring
- 12 x 3.5" hot-swap SAS/SATA drive bay with SES3, Optional 2 x 2.5" hot-swap drive bay
- 3 x 8cm high-performance PWM fan(s)
- 1200W/1000W Titanium Power Supply W/PMbus

Processor/Cac	he	
(Single AMD EPYC™ 7001/7002* series Processor *Board revision 2.x required) Socket SP3 Cores:Up to 32 Cores, Up to 64 Cores Board revision 2.x required)	
Chipset		
Chipset	System on Chip	
System Memor	у	
Memory Capacity	8 DIMM slots Supports up to 1TB Registered ECC DDR4 2666MHz SDRAM in 8 DIMMs, Supports up to 2TB Registered ECC DDR4 3200MHz SDRAM (Board revision 2.x required), 8-channel memory bus	
Expansion Slot	S	
PCI-Express	3 PCI-E 3.0 x8, 3 PCI-E 3.0 x16 M.2:Interface: PCI-E 3.0 x4, Form factor: 2280, 22110,Key: M-key	
Integrated O	nboard	
SATA	16 SATA3 (6 Gbps) ports	
LAN	2 RJ45 Gigabit Ethernet LAN ports, 1 RJ45 Dedicated IPMI LAN port	
Add-on Opti	ons	
Raid Card:	Optional	
Optical Drive:	None	





rone

Front Panel		
LEDs	2 Network Activity LEDs, Fan Fail/System Over Heat LED, HDD activity LED, Power Status LED, Unit Identification (UID) LED	
Buttons	Power On/Off button, System Reset Button	
Drive Bays		
HDD Bays	12 x 3.5"" hot-swap SAS/SATA drive bay with SES3	
	Optional 2 x 2.5"" hot-swap drive bay	
Power Supply		
1200W/1000W Titanium Power Supply W/PMbus		
Cooling System		
3 x 8cm high-performance PWM fan(s)		
Form Factor		
Form Factor	211 Backmount	

Form Factor	2U Rackmount
Dimensions:	Height : 3.5" (89 mm), Width :17.2" (437 mm) , Depth :25.5" (647 mm)

Email : info@tyronesystems.com For more/current product information, visit www.tyronesystems.com

AMD the AMD logo inside are trademarks of Advanced Micro Devices in US and / Or other Countries

specifications subject to change without notice. Picture used for representation purpose only and the actual product may differ in looks .All other brands and names are the property of their respective owners