Tyrone Camarero Specifications

Camerero: SSI100C3A-48

Key Features

Deep Learning/AI/Machine Learning Development

- Single Socket P+ (LGA-4189), 3rd Gen Intel® Xeon® Scalable processors, Support CPU TDP 270W, Up to 38C/76T "
- Intel® C621A '
- 16 DIMM slots, UP to 4TB: 16x 16 GB DRAM
- 4 PCI-E 4.0 x16, 3 PCI-E 4.0 x8 (in x16 slot), M.2 Interface: 4 PCI-E 4.0 x4, Form Factor: 2260/2280/22110 Key: M-Key, M.2 support to RAID 0,1, 5, 10, VROC key is required for RAID"
- Intel C621A controller for 8 SATA3 (6 Gbps) ports; RAID 0,1,5,10
- 1x 10GBase-T, 1x 1GbE, and dedicated IPMI LAN ports
- 4 or 8x 3.5" fixed drive bays, Peripheral Bays: 3x 5.25" drive bays
- 2x 80mm Fan(s), 4x 92mm Fan(s)
- 1200W (1 + 1) /2200W Redundant (1+1) Power Supply
 Optional: 500W/1200W Single multi output Power Supply.







Processor/Cac	he
---------------	----

Processor Single Socket P+ (LGA-4189), 3rd Gen Intel®

Xeon® Scalable processors, Support CPU

TDP 270W, Up to 38C/76T

Chipset

Chipset Intel® C621A

System Memory

Memory Capacity

16 DIMM slots, UP to 4TB: 16x 16 GB

DRAM

Expansion Slot

PCI-Express 4 PCI-E 4.0 x16, 3 PCI-E 4.0 x8 (in x16 slot),

M.2 Interface: 4 PCI-E 4.0 x4, Form Factor: 2260/2280/22110 Key: M-Key, M.2 support to RAID 0,1, 5, 10, VROC key is required for

RAID

Integrated Onboard:

SATA 8 SATA (6Gbps) port(s)

Network Connectivity 1x 10GbE BaseT with Marvell AQC113C, 1x 1GbE BaseT with Intel® I210-AT, 1x 1GbE BaseT with Realtek RTL8211F PHY (dedicated IPMI)

Add-on Options

Raid Card Optional

Optical Drive

Optional

Front Panel

LED HDD activity, Network activity, Power On

,System Overheat / Fan Fail LED

Buttons Power On/Off, System Reset

Drive bays

HDD Bays 4 or 8x 3.5" fixed drive bays

Peripheral Bays 3x 5.25 drive bays

Power Supply

Power Supply 1200W (1 + 1) /2200W Redundant (1+1)

Power Supply

Optional: 500W/1200W Single multi

output Power Supply.

Cooling System

2x 80mm Fan(s), 4x 92mm Fan(s)

Form Factor

Form Factor 4U rackmount/Tower

Email: Info@tyronesystems.com
For more/current product information, Visit
www.tyronesystems.com

Intel, the Intel logo, the Intel Inside logo, Xeon, and Intel Xeon Phi are trademarks of Intel Corporation in the U.S and/Or other Countries

Specifications subject to change without notice. Picture used for representation purpose only and the actual product may differ in looks. All other brands and names are the properties of their respective owners