Tyrone Camarero Specifications

Tyrone

Camarero SSI100C3W-28

Key features

Data Center Optimized, Database Processing and Storage, Network Appliance

- Single Socket P+ (LGA-4189), 3rd Gen Intel® Xeon® Scalable processors, Support CPU TDP 270W, Up to 36C/72T; Up to 60MB Cache
- Intel® C621A
- Memory Capacity: 8 DIMM slots, Up to 2TB: 8x 256 GB DRAM, Up to 3TB: 4x 256 GB DRAM and 4x 512 GB PMem

Memory Type: 3200/2933/2666MHz ECC DDR4 RDIMM;LRDIMM, Intel® Optane™ persistent memory 200 series

- 2 PCI-E 4.0 x16 (FHFL) slots, 2 PCI-E 4.0 x8 (LP) slots
- Intel® Ethernet Controller X550 2x 10GbE RJ45
- 8x hot-swap 3.5" SATA3 drive bays, SAS3 with additional SAS controller card, Optional 2x 2.5" Gen4
 NVMe drives at rear; Onboard 1x NVMe/SATA M.2
- 3 heavy duty PWM 80x80x38mm Fan(s)
- Redundant Platinum 600W/650W Power Supply





Processor/Cache

Processor Single Socket P+ (LGA-4189), 3rd Gen Intel®

Xeon® Scalable processors, Support CPU TDP 270W, Up to 36C/72T; Up to 60MB Cache

Chipset

Chipset Intel® C621A

System Memory

8 DIMM slots, Up to 2TB: 8x 256 GB DRAM,

Up to 3TB: 4x 256 GB DRAM and 4x 512 GB

Memory Capacity PMem

Memory Type: 3200/2933/2666MHz ECC DDR4 RDIMM;LRDIMM, Intel® Optane™

persistent memory 200 series

Expansion Slots

PCI-Express 2 PCI-E 4.0 x16 (FHFL) slots,

2 PCI-E 4.0 x8 (LP) slots

Integrated Onboard

SATA 10 SATA (6Gbps) port(s) ,RAID 0/1/5/10

support

LAN 1 RJ45 Dedicated IPMI LAN port, 2 RJ45

10GBase-T LAN ports

Add-on Options

Raid Card Optional
Optical Drive Optional

Front Panel

LEDs Device Activity, LAN 1 Activity, LAN 2 Activity,

Power Failure LED, Power status,

System information

Buttons Power On/Off, System Reset

Drive Bays

HDD Bays 8x 3.5"" SATA drive bays

(2x 2.5"" NVMe dedicated) M.2: 1x PCI-E 3.0 x 4 and SATA,

M-key, 2280, 22110

Peripheral Drives 2x 2.5" drive bays

Power Supply

Redundant Platinum 600W/650W Power Supply

Cooling System

3 heavy duty PWM 80x80x38mm Fan(s)

Form Factor

Form Factor 2U Rackmount

Dimensions: Height: 3.5" (89 mm),

Width: 17.2" (437 mm), Depth: 25.5" (647 mm)

Email: info@tyronesystems.com
For more/current product information, visit
www.tyronesystems.com

intel, the Intel logo, the Intel Inside logo, Xeon, and Intel Xeon Phi are trade marks of intel Corporation in the U.S and/Or other Countries