

Tyrone Camarero Specifications

Tyrone

Camerero: SSI200F0A-34

Key Feature

UP mid-tower workstation for 3D and VR content development
2D/3D Content Creation, VR Content Development

- Socket E (LGA4677) support Intel® Xeon® W-2400 processors
 - Intel® W790
 - 8 DIMMs
 - 1x 1GbBaseT, 1x 10GbBaseT
 - 4 3.5" SATA3 drive bays; ; 2 M.2 NVMe
 - 1x 120mm Fan(s), 1x 120mm Fan(s)
 - 500W/1200W single/redundant multi output power supply
- Optional:** 1x 1200W Platinum Level (90%) power supply



Processor/Cache		Front Panel	
Processor	Single Socket E (LGA4677) Intel® Xeon® W-2400 processors	LED	HDD activity LED
Chipset	Intel® W790	Buttons	Power On/Off button
System Memory		Ports	1 VGA port(s) and Audio port
Memory Capacity	8 DIMM slots Up to 1TB: 8x 128 GB DRAM Memory Type: 4800MHz ECC DDR5 RDIMM / LRDIMM	Drive bays	
Expansion Slot		Drive bays	4x 3.5" SATA drive bays, M.2 2x PCIe 5.0 x4.
PCI-Express	1 PCIe 4.0 x4 slot(s) 3 PCIe 5.0 x16 slot(s)	Peripheral Bays	2x 5.25" drive bays
Integrated Onboard		Power Supply	
IPMI	Support for Intelligent Platform Management Interface v.2.0 IPMI 2.0 with virtual media over LAN and KVM-over-LAN support	Power Supply	500W/1200W single/redundant multi output power supply Optional :1x 1200W Platinum Level (90%) power supply
Network Connectivity	1 RJ45 10GbE with Marvell® AQC113, 1 RJ45 1GbE with Intel® I210-AT	Cooling System	
		Fans	1x 120mm Fan(s), 1x 120mm Fan(s)
		Form Factor	
		Form Factor	5U/ Mid Tower
		Email : Info@tyronesystems.com For more/current product information, Visit www.tyronesystems.com	