# Tyrone Camarero Specifications

# Camarero SSZOTR-54L

## **Key features**

- 8th Generation Intel® Core™ i7(8086K and 8700K are not supported)/i5/i3/Pentium®/Celeron® Processor., Single Socket H4 (LGA 1151) supported, CPU TDP support Up to 120W TDP
- Up to 64GB Unbuffered non-ECC UDIMM, in 4 DIMM slots (Limited to Gen 8th series and Gen 9th core i3, Pentium and Celeron) Up to 128GB Unbuffered non-ECC UDIMM, in 4 DIMM slots (Limited to Gen 9th core i5/i7/i9)
- 2 PCI-E 3.0 x16 slots (16/NA or 8/8),1 PCI-E 3.0 x4,3 PCI-E 3.0 x1,M.2 Interface: 1 PCI-E 3.0 x4 and 1 PCI-E 3.0 x4M.2 Form Factor: 2260/2280/22110, 2260/2280/22110, M.2 Key: M-Key, M-Key (RAID 0,1 support)
- 1 DP (DisplayPort) port, 1 HDMI port, 1 DVI D port, DP up to 1.2; HDMI up to 1.4b
- Intel® Z370 Express controller for 6 SATA3 (6 Gbps) ports; RAID 0,1,5,10
- Single LAN with Intel<sup>®</sup> single Ethernet PHY i219V
- External: 5.25" x 4, 3.5" x 1; Internal: 3.5" x 5 or 2.5" x5
- Front: 120 x 25 mm x1 PWM Fan, Rear: 120 x 25 mm x1 PWM Fan
- 500/1200W Single PS, 80Plus Platinum







#### Processor/Cache

8th Generation Intel® Core™ i7(8086K Processor

and 8700K are not supported)/i5/i3/ Pentium®/Celeron® Processor., Single Socket H4 (LGA 1151) supported, CPU

TDP support Up to 120W TDP

## Chipset

Chipset Intel® Z370 Express

#### **System Memory**

Memory Capacity Up to 64GB Unbuffered non-ECC UDIMM,

> in 4 DIMM slots (Limited to Gen 8th series and Gen 9th core i3, Pentium and Celeron) Up to 128GB Unbuffered non-ECC UDIMM, in 4 DIMM slots (Limited to

Gen 9th core i5/i7/i9)

## **Expansion Slots**

2 PCI-E 3.0 x16 slots (16/NA or 8/8), **PCI-Express** 

1 PCI-E 3.0 x4,3 PCI-E 3.0 x1,M.2 Interface: 1 PCI-E 3.0 x4 and 1 PCI-E 3.0 x4 M.2 Form Factor: 2260/2280/ 22110, 2260/2280/22110, M.2 Key: M-Key, M-Key (RAID 0,1 support)

## **Integrated On-Board**

SATA Intel® Z370 Express controller for 6 SATA3

(6 Gbps) ports; RAID 0,1,5,10

LAN 1 RJ45 Gigabit Ethernet LAN ports

## **Add-on Options**

Raid Card Optional **Optical Drive** None

#### Front Panel

LFDs Front Control Panel Power Switch,

System Reset

**Buttons** Power On/Off button

## **Drive Bays**

HDD bays External: 5.25" x 4, 3.5" x 1;

Internal: 3.5" x 5 or 2.5" x5

## **Power Supply**

500/1200W Single PS, 80Plus Platinum

## **Cooling System**

Front: 120 x 25 mm x1 PWM Fan, Rear: 120 x 25 mm x1 PWM

## **Form Factor**

Form Factor Tower/Convertable/5U Rackmount

560 x 200 x 430 mm (22"" x 7.9"" x 16.9"") Dimension

Email: info@tyronesystems.com For more/current product information, visit

www.tyronesystems.com

O Intel, the Intel logo, the Intel Inside logo, Xeon, and Intel Xeon Phi are trademarks of intel Corporation in the U.S and/Or other Countries
O Specifications subject to change without notice. Picture used for representation purpose only and the actual product may differ in looks .All other brands and names are the property of their respective owners