

Tyrone Camarero Specifications

Tyrone

Camerero: TDI100F0R-212

Key Feature

- Dual Socket Intel Ice Lake SP CPU, 3rd Gen Intel Xeon Scalable Processor, LGA4189
- (8)+(8) DIMM slots DDR4 ECC RDIMM/RDIMM 3DS/LRDIMM/LRDIMM 3DS 3200, Up to 2,048GB RDIMM/ 4,096GB LRDIMM/ 4,096GB RDIMM 3DS/LRDIMM 3DS *Follow latest Intel DDR4 Memory POR
- Intel C621A chipset
- 3 PCIe Gen. 4x16 + 2 PCIe Gen.4x8 slots
- 2 PCIe x8 SlimSASconnectors (NVMe)
- 2 NVMe 22110 / 2280 M.2 slots
- 2 1000Base-T LAN + 1 dedicate 1000Base-T IPMI ports
- AST2600 BMC with IPMI 2.0 & Redfish support
- Whisper-Quiet (<27dB)
- 12 x front loaded 2.5"/3.5" bays(SAS/SATA).
- CRPS PSU FSP 800/1200/1600W



Processor/Cache		Drive bays	
Processor	Dual Socket Intel Ice Lake SP CPU, 3rd Gen Intel Xeon Scalable Processor, LGA4189	HDD Bays	12 x front loaded 2.5"/3.5" bays(SAS/SATA).
Chipset		Power Supply	
Chipset	Intel C621A chipset	Power Supply	CRPS PSU FSP 800/1200/1600W
System Memory		Form Factor	
Memory Capacity	(8)+(8) DIMM slots DDR4 ECC RDIMM/RDIMM 3DS/LRDIMM/LRDIMM 3DS 3200, Up to 2,048GB RDIMM/ 4,096GB LRDIMM/ 4,096GB RDIMM 3DS/LRDIMM 3DS	Form Factor	2U Rackmount
Expansion Slot		Dimensions	
PCI-Express	3 PCIe Gen. 4x16 + 2 PCIe Gen.4x8 slots	Dimensions	660 x 436 x 87 mm
Integrated Onboard:		Email : Info@tyronesystems.com For more/current product information, Visit www.tyronesystems.com	
SATA	(3) Mini-SAS HD from PCH SATA-III		
LAN	Intel I210-AT		
Network Connectivity	IPMI 2.0 compliant baseboard management controller (BMC) / 10/100/1000 Mb/s MAC interface		
Add-on Options			
Raid Card	Optional		
Optical Drive	Optional		