

Tyrone Camarero Specifications

Tyrone

Camarero- TSI100F0A-34

Key Feature

- Supports 12th Gen Intel Core Processors (LGA1700)
- 6 Phase Power Design
- Supports 2 x DIMM Slots, DDR4 3200MHz, U-DIMM, Up to 64GB
- Intel H610 Chipset
- Graphics Output Options: 2 HDMI 1.4 & 1 DP1.4a
- 7.1 CH HD Audio Codec
- 4 SATA3
- 4 USB 3.2 Gen1 (2 Rear, 2 Front) , 6 USB 2.0 (4 Rear, 2 Front)
- 1 PCIe 4.0 x16, 2 PCIe 3.0 x1
- LAN Port
- 2x 5.25" External HDD Drive Bays & 4x 3.5" Internal HDD Drive Bays
- 1x Rear 12cm (1850 RPM) PWM Fan
- 600W Redundant Power supply



Processor/Cache

Processor Supports 12th Gen Intel Core™ Processors (LGA1700) 6 Power Phase design, Supports Intel Hybrid Technology, Supports Intel Turbo Boost Max 3.0 Technology, Support CPU: Alder Lake-S 65W

System Memory

Memory Capacity Supports 2 x DIMM Slots, DDR4 3200MHz, U-DIMM, Up to 64GB

Chipset

Chipset Intel H610 Chipset

Expansion Slot

Expansion Slot 1 PCIe 4.0 x16, 2 PCIe 3.0 x1, M.2 for SSD 1 x Support PCIe3.0 X4 (2242 & 2280)

Integrated Onboard:

SATA 4 SATA3

Graphics Output Options 2 HDMI 1.4 & 1 DP1.4a

Add-on Options

Raid Card Optional

Optical Drive Optional

Front Panel

LEDs Power status LED, HDD activity LED, 1 Network activity LEDs, System Overheat LED

Buttons PowerPower On/Off button

Ports 2x USB 3.0 Port(s)

Drive bays

HDD Bays Optional 4x 2.5" fixed drive bay, 4x 3.5" fixed drive bay

Peripheral Drives 2x standard 5.25" drive bay, 1x 3.5" internal fixed drive bay, 1x 90 degree rotatable drive cage

Power Supply

Power Supply 600W Redundant Power supply

Cooling System

Fans 1x Rear 12cm (1850 RPM) PWM Fan

Form Factor

Form Factor Mid-Tower Chassis

Dimensions

Dimensions (L x W x H) 190 x 150 x 84 mm

Email : Info@tyronesystems.com

For more/current product information, Visit

www.tyronesystems.com

Netweb Technologies India Ltd.

**#36, Neela Nivas, 1st and 3rd floor, Bowring hospital road,
Plain street, Shivajinagar, Bangalore - 560001
Ph no : 080 40540000**