

Tyrone Camarero Specifications

Tyrone[®]

Camarero DS40012R-224RTL

Key features

- Corporate Database, Database Processing & Storage, Enterprise Server, HPC, Data Center. iSCSI SAN
- 2nd Generation Intel® Xeon® Scalable Processors (Cascade Lake-SP), Intel® Xeon® Scalable Processors., Dual Socket P (LGA 3647) supported, CPU TDP support 205W, 3 UPI up to 10.4 GT/s
- Intel® C622 chipset
- Up to 4TB 3DS ECC RDIMM, DDR4-2933MHz; Up to 4TB 3DS ECC LRDIMM, DDR4-2933MHz, in 16 DIMM slots; Up to 2TB Intel® Optane™ DC Persistent Memory in memory mode (Cascade Lake only);
- 3 PCI-E 3.0 x16, 4 PCI-E 3.0 x8
- 24 Hot-swap 2.5" SAS3/SATA3 direct attached drive bays
- 3 Broadcom 3008 SAS3 AOC (IT mode)
- 2x 10GBase-T LAN ports with Intel X722 + PHY Intel X557
- Server remote management: IPMI 2.0 / KVM over LAN / Media over LAN
- 3 Hot-swap 8cm redundant PWM fans
- 1200W Redundant Power Supplies Titanium Level (96%)



Processor/Cache		Front Panel	
Processor	2nd Generation Intel® Xeon® Scalable Processors (Cascade Lake-SP), Intel® Xeon® Scalable Processors., Dual Socket P (LGA 3647) supported, CPU TDP support 205W, 3 UPI up to 10.4 GT/s	Led's	Power status LED, Hard drive activity LED, Network activity LEDs, System Overheat LED, Power fail LED
Chipset	Intel® C622 chipset	Buttons	Power On/Off button, System Reset button
System Memory		Drive Bays	
Memory Capacity	Up to 4TB 3DS ECC RDIMM, DDR4-2933MHz; Up to 4TB 3DS ECC LRDIMM, DDR4-2933MHz, in 16 DIMM slots; Up to 2TB Intel® Optane™ DC Persistent Memory in memory mode (Cascade Lake only);	HDD bays	24 Hot-swap 2.5" SAS3/SATA3 drive bays
Expansion Slots	3 PCI-E 3.0 x16, 4 PCI-E 3.0 x8	Optional	2 Optional Onboard NVMe M.2
Integrated On-Board		Power Supply	
SAS	SAS3 (12Gbps) via Broadcom 3008 AOC, 3 Broadcom 3008 controller	1200W Redundant Power Supplies Titanium Level (96%)	
SATA	SATA3 (6Gbps); RAID 0, 1, 5, 10	Cooling System	
LAN	2 RJ45 10GBase-T LAN ports, 1 RJ45 Dedicated IPMI LAN port	3 Hot-swap 8cm redundant PWM fans	
Add-on Options		Form Factor	
Optical Drive	None	Form Factor	2U Rackmount
		Width	17.2" (437mm),
		Height	3.5" (89mm),
		Depth	24.8" (630mm)
		<p>Email : info@tyronesystems.com</p> <p>For more/current product information, visit</p> <p>www.tyronesystems.com</p>	

© Intel, the Intel logo, the Intel Inside logo, Xeon, and Intel Xeon Phi are trademarks of Intel Corporation in the U.S and/or other countries
 © Specifications subject to change without notice. Picture used for representation purpose only and the actual product may differ in looks. All other brands and names are the property of their respective owners