

Tyrone Camarero Specifications

Tyrone®

Camarero DS4007R-436RT

Key features

- **Corporate Database, Database Processing & Storage, Enterprise Server, HPC, Data Center. iSCSI SAN**
- 2nd Generation Intel® Xeon® Scalable Processors (Cascade Lake-SP), Intel® Xeon® Scalable Processors., Dual Socket P (LGA 3647) supported, CPU TDP support 205W, 3 UPI up to 10.4 GT/s
- Intel® C622
- Up to 4TB 3DS ECC RDIMM, DDR4-2933MHz; Up to 4TB 3DS ECC LRDIMM, DDR4-2933MHz, in 16 DIMM slots; Up to 2TB Intel® Optane™ DC Persistent Memory in memory mode (Cascade Lake only);
- 3 PCI-E 3.0 x16, 4 PCI-E 3.0 x8 (slot 2 & 3 occupied by controller and JBOD expansion port)
- 36 Hot-swap 3.5" SAS3/SATA3 direct attached drive bays
- Broadcom 3108 SAS3 AOC
- 2x 10GBase-T LAN ports with Intel X557
- Server remote management: IPMI 2.0 / KVM over LAN / Media over LAN
- 3 Hot-swap 8cm redundant PWM cooling fans, 2 hot-swap 8cm rear exhaust PWM fans
- 1200W Redundant Power Supplies Titanium Level (96%)



Processor/Cache		Front Panel	
Processor	2nd Generation Intel® Xeon® Scalable Processors (Cascade Lake-SP), Intel® Xeon® Scalable Processors., Dual Socket P (LGA 3647) supported, CPU TDP support 205W, 3 UPI up to 10.4 GT/s	Led's	Power status LED, Hard drive activity LED, Network activity LEDs, System Overheat LED, Power fail LED
Buttons		Buttons	Power On/Off button, System Reset button
Chipset		Drive Bays	
Chipset	Intel® C622	HDD bays	36 Hot-swap 3.5" SAS3/SATA3 drive bays
		Optional	2 Optional Onboard NVMe M.2
System Memory		Power Supply	
Memory Capacity	Up to 4TB 3DS ECC RDIMM, DDR4-2933MHz; Up to 4TB 3DS ECC LRDIMM, DDR4-2933MHz, in 16 DIMM slots; Up to 2TB Intel® Optane™ DC Persistent Memory in memory mode (Cascade Lake only);	1200W Redundant Power Supplies Titanium Level (96%)	
Expansion Slots		Cooling System	
PCI-Express	3 PCI-E 3.0 x16, 4 PCI-E 3.0 x8 (slot 2 & 3 occupied by controller and JBOD expansion port)	3 Hot-swap 8cm redundant PWM cooling fans, 2 hot-swap 8cm rear exhaust PWM fans	
Integrated On-Board		Form Factor	
SAS	SAS3 (12Gbps) via Broadcom 3108 AOC; HW RAID. RAID 0, 1, 5, 6, 10, 50, 60	Form Factor	4U Rackmount
SATA	SATA3 (6Gbps); RAID 0, 1, 5, 10	Height-	7" (178mm),
LAN	2 RJ45 10GBase-T LAN ports, 1 RJ45 Dedicated IPMI LAN port	Width-	17.2" (437mm),
		Depth-	27.5" (699mm)
Add-on Options		<p>Email : info@tyronesystems.com</p> <p>For more/current product information, visit www.tyronesystems.com</p>	
Optical Drive	None		

© Intel, the Intel logo, the Intel Inside logo, Xeon, and Intel Xeon Phi are trademarks of Intel Corporation in the U.S and/or other countries
 © Specifications subject to change without notice. Picture used for representation purpose only and the actual product may differ in looks. All other brands and names are the property of their respective owners