

# Tyrone Camarero Specifications

**Tyrone**<sup>®</sup>

## Camarero SS300TR-14R

### Key features

- Single socket R3 (LGA 2011) supports Intel® Xeon® processor E5-2600v4/ v3 family
- Intel C612 chipset
- Up to 1TB ECC 3DS LRDIMM , up to DDR4- 2400MHz ; 8x DIMM slots
- 1x PCI-E 3.0 x16 slot
- Intel® i350-AM2 Dual port GbE LAN
- Integrated IPMI 2.0 and KVM with Dedicated LAN
- I/O ports: 1x VGA, 2x COM, 2x USB 3.0, 4x USB 2.0
- 4x 3.5" Hot-swap SATA3 drive bays
- 4x 40x28mm 4-pin PWM Cooling Fans
- 400W (1+1) Redundant Short-depth 80Plus Gold-level power supplies



Processor/Cache		Front Panel	
Processor	Single socket R3 (LGA 2011) supports Intel® Xeon® processor E5-2600v4/ v3 family	LED Indicators	Power LED,Hard drive activity LED, 2x Network activity LEDs,System Overheat LED
Buttons		Buttons	Power On/Off Button,System Reset Button
Chipset		Drive Bays	
Chipset	Intel C612 chipset	HDD bays	4x 3.5" Hot-swap SATA3 drive bays
		Peripheral Drives	Optional slim optical device bay, optional FDD/USB bay. 2x 2.5" Fixed drives internal
System Memory		Power Supply	
Memory Capacity	8x 288-pin DDR4 DIMM slots, Up to 1TB ECC 3DS LRDIMM, Up to 512GB ECC LRDIMM, Up to 256GB ECC RDIMM		400W (1+1) Redundant Short-depth 80Plus Gold-level power supplies
Expansion Slots		Cooling System	
PCI-Express	1x PCI-E 3.0 x16 slot		4x 40x28mm 4-pin PWM Cooling Fans
Integrated On-Board		Form Factor	
SATA	SATA3 (6Gbps) via C612 controller. RAID 0, 1, 10 support; 5 supported under Windows	Form Factor	1U Rackmountable
LAN	2x RJ45 Gigabit Ethernet LAN ports 1x RJ45 Dedicated IPMI LAN port		Width: 17.2" (437 mm), Height: 1.7" (43mm) , Depth: 19.85" (503mm)
Add-on Options		<p><b>Email : <a href="mailto:info@tyronesystems.com">info@tyronesystems.com</a></b></p> <p><b>For more/current product information, visit</b></p> <p><b><a href="http://www.tyronesystems.com">www.tyronesystems.com</a></b></p>	
Raid	Optional		
Optical Drive	Optional		